




CLASS ALL
A DC

An indoor unit which fits directly to the ceiling, this air conditioner is lightweight, slim and extremely quiet. The swing louvres create a steady flow of air over a wide area, making it economical and effective. Because of their design, ceiling-suspended units can be installed quickly, simply and with minimal disruption. A long-life washable air filter is included for easy maintenance.



- Easy to fit to any ceiling
- Adjustable air flow
- Fresh air intake
- Auto shut flaps
- Cooling/heating
- Ultra quiet
- Washable air filter
- Easy-to-use remote controller
- Quick and easy installation



		Inverter Heat Pump - R410A		
Indoor		ABYA30LB	ABYA36LB	ABYA45LC
Outdoor		AOYA30LB	AOYA36LB	AOYA45LB
Energy Label (Cooling / Heating)		A / A	A / A	A / A
Auto Double Swing		✓	✓	✓
Auto Air Flow Adjustment		✓	✓	✓
Auto Restart		✓	✓	✓
Auto-Changeover		✓	✓	✓
Connectable Fresh Air Duct		✓	✓	✓
Economy Mode		✓	✓	✓
Sleep Timer		✓	✓	✓
Program Timer		✓	✓	✓
Connectable Fresh Air Duct		✓	✓	✓
Nominal Capacity (kW)	Cooling	8.50	9.40	12.50
	Heating	10.00	11.20	14.00
Moisture Removal	l/h	2.50	3.00	4.50
Dimensions (HxWxD) mm	Inner	240x1660x700	240x1660x700	240x1660x700
	Outer	830x900x330	830x900x330	1290x900x330
Net Weight (kg)	Inner	46	46	46
	Outer	62	62	98
Room Air Circulation (high) m ³ /h	Inner	1660	1900	2100
	Outer	3600	3600	6600
Power Supply	VPHz	230/1/50	230/1/50	230/1/50
Power Supply To		Outdoor	Outdoor	Outdoor
Running Current A	Cooling	11.60	12.80	17.00
	Heating	12.10	13.20	16.50
Starting Current	A	15.00	15.00	15.00
Fuse Rating	A	30	30	30
Power Consumption kW	Cooling	2.65	2.93	3.89
	Heating	2.77	3.02	3.77
Interconnecting Cable		3 + E	3 + E	3 + E
Remote Control Type		Wireless	Wireless	Wireless
Noise Levels (dB(A) Cooling)	Indoor Q/L/M/H	32 / 37 / 43 / 45	32 / 37 / 43 / 47	34 / 39 / 45 / 49
	Outdoor	53	54	55
Max Pipe Length	m	50	50	50
Max Height Difference	m	30	30	30
Refrigerant Charge	m	20	20	20
Pipe Size (inches)	Gas	5/8 (15.88mm)	5/8 (15.88mm)	5/8 (15.88mm)
	Liquid	3/8 (9.52mm)	3/8 (9.52mm)	3/8 (9.52mm)
Operating Range (°C)	Cooling	-15 ~ 46	-15 ~ 46	-15 ~ 46
	Heating	-15 ~ 24	-15 ~ 24	-15 ~ 24
Refrigerant		R410A	R410A	R410A

Only A / A rated systems are eligible for ECA (refer to ECA website for confirmation)

Cooling & Heating capacities are based on the following conditions:

Cooling: Indoor Temp.: 27°C DB/19°C WB, Outdoor Temp.: 35°C DB/24°C WB

Heating: Indoor Temp.: 20°C DB, Outdoor Temp.: 7°C DB

Note: Fuse ratings shown are only for information. Any fuses or MCB's installed on-site should be sized in accordance with I.E.E. regulations.

For full installation details please contact FG Eurofred your local distributor

Optional Parts:

Wired Remote Controller (UTB-YUD)
Drain Pump Unit (UTR-DPB24T)

Distributed by:



The company reserves the right to make any variation in specification to the equipment described or to withdraw or replace products without prior notification or public announcement. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form any part of any contract. For full installation details please contact FG Eurofred or your local distributor.

